USER MANUAL




Thank you for choosing Better Bathrooms.

Please read this manual before installing your product and keep for future reference.



BACK LIT PILL SHAPED MIRROR (500 x 1000mm)



VENBB1000 (Brushed Brass)
VENMB1000 (Matt Black)

- SINGLE-PERSON ASSEMBLY
- LED LIGHT
- IP44 INGRESS PROTECTION

CONGRATULATIONS ON YOUR PURCHASE

Our aim at Better Bathrooms is to bring you extraordinary bathroom products for less.

If you're after a modern, traditional, or totally unique bathroom style, we have the fittings and fixtures to bring your ideas to life so you can fall in love with your space every day.

We hope your new product goes above and beyond your expectations. However, should any problems occur, please:

- Log in to your account and contact our customer services team via your self-service portal betterbathrooms.com/CustomerAccount/Login
- Contact us via betterbathrooms.com/contact/contact-us

CONTENTS


SAFETY	3	
BATHROOM ZONES	4	
PARTS SUPPLIED	4	
TOOLS REQUIRED	5	
PRODUCT OVERVIEW	5	
INSTALLING THE MIRROR	6	
PRODUCT DIMENSIONS		
OPERATION		
TECHNICAL SPECIFICATIONS	8	
DISPOSAL	9	

SAFETY

- A qualified electrician should install this mirror.
- This fitting is only suitable for connection to a 220-240V~50/60Hz earthed supply in accordance with current IEE wiring regulations and should be installed in accordance with local Building Regulations.
- This is for domestic, indoor use only.
- The fitting should be connected to a dedicated lighting circuit, which must be protected by a 5-amp fuse (or a 6-amp miniature circuit breaker).
- Before installing the fitting, ensure the mains supply is switched off and that the appropriate fuse is removed (or the appropriate circuit breaker is switched off) before commencing installation. Ensure that measures are taken to prevent the supply from being inadvertently reconnected.
- If there is a "Minimum Distance" Label, please do not allow Flammable Materials to rest within that distance from the unit.
- This product may contain delicate parts be careful during handling and maintenance to avoid breakage.
- Any modification to the fitting will invalidate the warranty and may render the product unsafe.
- A defective appliance may cause electric shock. Never switch on a defective or damaged appliance. Disconnect the appliance from the mains before seeking assistance.
- This product is IP44 rated, and no part of the installation is allowed to be within bathroom Zones 0 or 1. Installation is permitted within Zone 2.
- This product must be earthed. Before commencing installation, ensure that there are no pipes or wires located behind the wall that may be damaged during drilling.
- Ensure that the hanging location has been decided upon and marked clearly to avoid unwanted damage to the wall due to incorrect positioning.
- Check that the mirror is not damaged prior to installation.
- Take care of unpacking, and do not use a sharp blade to open it, as this may damage the mirror and void your warranty.
- Installation must only be carried out by a qualified professional or electrician.
- Once installed, silicon can be applied between the cabinet and the wall around the unit. Don't seal the bottom of the cabinet, as this may allow water to accumulate behind it.
- If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similarly qualified person in order to avoid a hazard.


- The light source of this luminaire is not replaceable; when the light source reaches its end of life, the whole luminaire shall be replaced.
- To reduce the risk of strangulation, the flexible wiring connected to this luminaire shall be effectively fixed to the wall if the wiring is within arm's reach.

BATHROOM ZONES




Zone 0:	The interior of the bathtub or shower basin.	
Zone 1:	The area around the bathtub or shower basin up to a	
zone 1:	height of 2.25m above the floor	
Zone 2:	The area stretching to 0.6m outside the bath or shower	
	and above the bath or shower if over 2.25m	

PARTS SUPPLIED




PLEASE NOTE: It is the installer's responsibility to ensure that the fittings are suitable for the type of wall. Alternative fittings may be required (not supplied). If unsure, professional advice should be sought.

TOOLS REQUIRED



PRODUCT OVERVIEW




INSTALLATION


IMPORTANT: Before commencing installation, ensure that there are no pipes or wires located behind the wall that you will be drilling into. Since this item is equipped with a sensor, it must be installed at least 20 cm above any objects to avoid interference with its functionality.

Please see the next page for product dimensions; alternatively, you can use the holes on the back of the mirror as a guide.

- Ensure that the hanging location has been decided upon and marked clearly to avoid unwanted damage to the wall due to incorrect positioning.
- Check that the mirror is not damaged prior to installation.
- Take care of unpacking, and do not use a sharp blade to open it, as this may damage the mirror and void your warranty.
- **IMPORTANT:** The power must be disconnected when installing and performing any maintenance.
- 1. Mark the drill hole spots on your wall using a spirit level to ensure they are level.
- 2. Drill the holes in the wall and insert two wall plugs.
- 3. Insert the screws, leaving these protruding by 3mm. It is recommended that these levels be checked again with the spirit level.
- 4. Connect the mirror to your electrics via a fuse spur following all local regulations and the wiring diagram provided. Then, turn the power back off via the installed switch.
- 5. Hang the mirror onto the screws. Re-connect the power.




PRODUCT DIMENSIONS



OPERATION

Your mirror comes with an infrared sensor located in the middle of the bottom. To activate the light and demisting pad, move your hand across the sensor once at a distance of around 5cm.



To turn it off, move your hand across the sensor again. Hold your hand in front of the sensor to change the colour temperature of the light.

CLEANING AND MAINTENANCE

Never use products containing bleach or abrasive cleaners, as this will have a detrimental effect on the appearance and lifespan of the product.

Use a clean microfibre cloth to clean the mirror.

TECHNICAL SPECIFICATION

Model	VENBB1000 / VENMB1000
WxHxD (mm)	500x1000x41
Net Weight (Kg)	6.5
Power Cord length (cm)	90
Rated Power (W)	45W
IP Rating	IP 44
Input	220 V-240 V 50/60 Hz

This product contains a light source of energy efficiency class F.

DISPOSAL

Recycling facilities are now available for all customers at which you can deposit your old electrical products. Customers will be able to take any old electrical equipment to participating sites run by their local councils.



Please remember that this equipment will be further handled during the recycling process, so please be considerate when depositing your equipment. Please get in touch with the local council for details of your local household waste recycling centres.

At the time of printing the product contains no substances listed within Annex XIV of the Reach Regulations (EC) 1907/2006. In accordance with Article 59 of the same regulation, the following substances are contained within the product at permitted levels: Cadmium.

As a responsible manufacturer, we monitor the regulations to ensure continued compliance. Further information can be provided upon request.

For more information

- visit betterbathrooms.com
- email customerservices@buyitdirect.co.uk
- call 0330 390 3062
- write to Trident Business Park, Neptune Way, Huddersfield, HD2 1UA

